



ITATOOLS

A GREENBRIDGE COMPANY



PLASTIC & STEEL STRAPPING TOOLS

MAKE YOUR WORLD SAFE
PLASTIC & STEEL STRAPPING TOOLS



20 years
of experience



Made
in Italy



Technical
support



Distributors
all over the world



ITATOOLS srl is an Italian Manufacturer of Strapping tools. Suitable for plastic, steel and textile strap, our product portfolio includes a complete range of battery operated, pneumatic and manual strapping tools that can be used in several sectors and for multiple applications. Established in 2006, Itatools boasts a team of professionals who have been operating successfully in the strapping sector for over 30 years. Commercial and Administrative offices, Technical department, and Production are located in the company headquarters, in the neighborhood of Milan. The experience gained on the market, the quality assured, the reliability and competitiveness of the products led to a rapid growth of the Company on the International market. Today Itatools can be considered one of the leading manufacturers of strapping tools on a global scale.

ITATOOLS offers a complete range of battery operated, pneumatic and manual strapping tools to meet any strapping need for plastic, metal and textile strapping.

- **DESIGN & PRODUCTION MADE IN ITALY.** Strapping tools are designed, developed and produced internally. Every single strapping tool is made in Italy, which is synonymous of high quality.
- **TEST & TRIALS.** Each component and every tool are tested to guarantee the quality and reliability that distinguishes us.
- **TECNICAL SUPPORT.** Itatools offers a continuous technical support and provides after-sales assistance for the maintenance of the tools produced.
- **GLOBAL VIEW.** Itatools boasts a network of distributors on a global scale, in order to ensure widespread market coverage and anticipate the sector's trend.
- **EXPERIENCE.** Thanks to the experience gained in the sector, Itatools offers high quality, reliable and innovative strapping tools on the international market.
- **CONTINUOUS DEVELOPMENT.** The creativity and competence of the technical team, which designs and develops each tool, allows Itatools to be always in line with the times in a continuous evolving market.

EVOLUTION | Battery strapping tools

For **PP & PET** strap

ITA EVO

Features

3 Operating modes: Automatic
Semi Automatic / Manual

Opening lever free

Soft & Standard
tensioning mode

BENEFITS

- Wide range & adjustable tension
- Easy to be used
- Ergonomic design & perfectly balanced
- Friction weld and high seal efficiency
- Strong and well protected motor housing
- Li-Ion 18V - 5Ah battery

	ITA EVO 13/16	ITA EVO 16/19
➤	PP & PET (Smooth / Embossed)	
Strap Type	PP & PET (Smooth / Embossed)	
Strap Width	13 mm / 16 mm	16 mm / 19 mm
Strap Thickness	0,5 ÷ 1,05 mm	0,7 ÷ 1,30 mm
Tension Force Range – Standard mode	650N / 2500N	1150N / 4500N
Tension Force Range – Soft mode	300N / 525N	600N / 1150N
Tensioning Speed	11 mt / min	6 mt/ min
Battery	Li-Ion 18V - 5Ah	Li-Ion 18V - 5Ah
Dimensions	330x135x142 mm	330x140x142 mm
Weight (with battery)	4,4 kg	4,6 kg
Sealing	Friction weld sealing	
Joint Strength	75% of breaking strength (Variable according to the strap type)	





► ITA EVO



Search for **Itatools**



Bluetooth
connection



Mobile App
for Android & iOS



Opening
lever free



3 Operating
modes

BATTERY TOOLS | For PP & PET strap

Three operating modes

NEW

Features

3 Operating modes: Automatic
Semi Automatic / Manual

Easy to be used

Digital control panel

Brushless motor technology

BENEFITS

- Wide range of straps & Adjustable tension
- Lightweight and well balanced
- One hand operating tools
- Easy access to wearing parts
- Strong and well protected motor housing
- **NEW!** Li-Ion 18V - 5Ah battery (ITA 24 - ITA 25)
Higher number of duty cycles

	ITA 24 - 18V	ITA 25 - 18V	ITA 27
➤	PP & PET (Smooth / Embossed)		
Strap Type	PP & PET (Smooth / Embossed)		
Strap Width	13 mm / 16 mm	16 mm / 19 mm	19 mm / 25 mm / 32 mm
Tension Force – Min	300N	500N	2700N
Tension Force – Max	2500N	4500N	7000N
Tensioning Speed	10 ÷ 16 mt / min	10 ÷ 12 mt / min	8 mt / min
Battery	Li-Ion 18V - 5Ah	Li-Ion 18V - 5Ah	Li-Ion 36V - 2,5Ah
Dimensions	340x150x160 mm	340x150x160 mm	300x150x200 mm
Weight (with battery)	4,5 kg	4,5 kg	6,4 kg
Sealing	Friction weld sealing		
Joint Strength	75% of breaking strength (Variable according to the strap type)		



ITA 24 - 18V



▶ ITA 24 - 18V

STRAP TYPE	WIDTH	THICKNESS
PP	13 mm	0,5 ÷ 1,05 mm
PP	16 mm	0,5 ÷ 1,05 mm
PET	13 mm	0,5 ÷ 1,05 mm
PET	16 mm	0,5 ÷ 1,05 mm

ITA 25 - 18V



▶ ITA 25 - 18V

STRAP TYPE	WIDTH	THICKNESS
PP	16 mm	0,8 ÷ 1,05 mm
PP	19 mm	0,7 ÷ 1,30 mm
PET	16 mm	0,8 ÷ 1,05 mm
PET	19 mm	0,7 ÷ 1,30 mm

ITA 27



▶ ITA 27

STRAP TYPE	WIDTH	THICKNESS
PET	19 mm*	1,0 ÷ 1,40 mm
PET	25 mm	0,8 ÷ 1,30 mm
PET	32 mm	0,8 ÷ 1,30 mm

* 19 mm Guidestrap Kit available on request



BATTERY TOOLS | For PP & PET strap

Li-Ion 18V - 5Ah - Manual operating mode

NEW

Features

Manual operating mode
 Easy to be used
 Strap size change
 without guide replacement
 Digital control panel

BENEFITS

- Adjustable tension
- Lightweight and one hand operating tool
- Friction weld and high seal efficiency
- Strong and well protected motor housing
- **NEW!** Li-Ion 18V - 5Ah battery
Higher number of duty cycles

	ITA 20 - 18V	ITA 21 - 18V	ITA 23 - 18V
➤	PP & PET (Smooth / Embossed)		
Strap Type			
Strap Width	13 mm / 16 mm	16 mm / 19 mm	16 mm / 19 mm
Tension Force – Min	600N	1100N	1900N
Tension Force – Max	2200N	3500N	5000N
Tensioning Speed	12 mt / min		
Battery	Li-Ion 18V - 5Ah	Li-Ion 18V - 5Ah	Li-Ion 18V - 5Ah
Dimensions	300x140x185 mm	300x140x185 mm	300x140x185 mm
Weight (with battery)	4,2 kg	4,3 kg	4,3 kg
Sealing	Friction weld sealing		
Joint Strength	75% of breaking strength (Variable according to the strap type)		



ITA 20 - 18V



▶ ITA 20 - 18V

STRAP TYPE	WIDTH	THICKNESS
PP	13 mm	0,5 ÷ 1,05 mm
PP	16 mm	0,5 ÷ 1,05 mm
PET	13 mm	0,5 ÷ 1,05 mm
PET	16 mm	0,5 ÷ 1,05 mm

ITA 21 - 18V



▶ ITA 21 - 18V

STRAP TYPE	WIDTH	THICKNESS
PP	16 mm	0,8 ÷ 1,05 mm
PET	16 mm	0,8 ÷ 1,05 mm
PET	19 mm	0,7 ÷ 1,27 mm

ITA 23 - 18V



▶ ITA 23 - 18V

STRAP TYPE	WIDTH	THICKNESS
PET	16 mm	1,05 mm
PET	19 mm	0,8 ÷ 1,27 mm



ENTRY LEVEL BATTERY TOOL

For **PP & PET** strap
Manual operating mode

Features

Manual operating mode
Adjustable tensioning force
Adjustable welding time
Digital control panel
Strong and well protected motor housing

BENEFITS

- Economical & easy to be used
- High capacity 18V battery
- Lightweight and one hand operating tools
- Friction weld and high seal efficiency
- Strap size change without guide replacement

ITA 22



➤ ITA 22

Strap Type	PP & PET (Smooth / Embossed)
Strap Width	13 mm / 16 mm
Tension Force – Min	600N
Tension Force – Max	1500N
Tensioning speed	8 mt / min
Battery	Li-Ion 18V - 5Ah
Dimensions	316x140x160 mm
Weight (with battery)	4,1 kg
Sealing	Friction weld sealing
Joint Strength	75% of breaking strength (Variable according to the strap type)

STRAP TYPE	WIDTH	THICKNESS
PP	13 mm	0,5 ÷ 1,05 mm
PP	16 mm	0,5 ÷ 1,05 mm
PET	13 mm	0,5 ÷ 0,8 mm
PET	16 mm	0,5 ÷ 0,8 mm





PNEUMATIC STRAPPING TOOLS

For **PP & PET** strap

Features

High resistance
Aluminium Cast Body

Durable and low
maintenance required

Suspension hook
already equipped

Suitable for a wide range
of plastic strap

BENEFITS

- Strong, Powerful and Reliable
- Friction weld and high seal efficiency
- Adjustable tension
- Easy to be used, even with one hand

	ITA 10	ITA 11	ITA 12	ITA 14	ITA 18
➤	PP & PET (Smooth / Embossed)				
Strap Type					
Strap Width	10 / 13 / 16 / 19 mm	13 / 16 / 19 mm	16 / 19 mm	25 / 32 mm	16 / 19 mm
Tension Force – Max (6.5 bar)	2500N	3500N	5000N / 6000N	5000N / 6000N	n.a.
Tensioning Speed	11 mt / min	9 mt / min	6 mt / min (5000N) 4 mt / min (6000N)	6 mt / min (5000N) 4 mt / min (6000N)	n.a.
Pressure range	4,5 ÷ 7 bar	4,5 ÷ 7 bar	4,5 ÷ 7 bar	6 ÷ 7 bar	4,5 ÷ 7 bar
Air consumption	Tensioning: 14 L/s				n.a.
Dimensions	280x150x175 mm	300x150x175 mm	300x150x175 mm	300x160x175 mm	250x130x120 mm
Weight	4,9 kg	5,6 kg	5,6 kg	5,8 kg	2,6 kg
Sealing	Friction weld sealing				
Joint Strength	75% of breaking strength (Variable according to the strap type)				



ITA10



▶ ITA 10

STRAP TYPE	WIDTH	THICKNESS
PP / PET	10 mm	0,4 ÷ 1,2 mm
PP / PET	13 mm	0,4 ÷ 1,2 mm
PP / PET	16 mm	0,4 ÷ 1,2 mm
PP / PET	19 mm	0,4 ÷ 1,2 mm

Tensioning with friction system for all versions

ITA11



▶ ITA 11

STRAP TYPE	WIDTH	THICKNESS
PET	13 mm	0,7 ÷ 1,4 mm
PP / PET	16 mm	0,7 ÷ 1,2 mm
PP / PET	19 mm	0,7 ÷ 1,2 mm

13 mm version: tensioning with friction system

ITA12



▶ ITA 12

STRAP TYPE	WIDTH	THICKNESS
PET	16 mm	1,0 ÷ 1,4 mm
PET	19 mm	1,0 ÷ 1,4 mm

ITA14



▶ ITA 14

STRAP TYPE	WIDTH	THICKNESS
PET	25 mm	0,8 ÷ 1,27 mm
PET	32 mm	0,8 ÷ 1,27 mm

ITA18



▶ ITA 18 - Welding device

STRAP TYPE	WIDTH	THICKNESS
PP / PET	16 / 19 mm	0,4 ÷ 1,4 mm

COMBINED PNEUMATIC STRAPPING TOOLS

For steel strap

Features

Wide range of tools
 For complete range
 of steel straps
 Single or double notch
 Manual or automatic tension

BENEFITS

- Robust and durable
- Low Maintenance Required
- Powerful and Fast
- Suspension hook already equipped

	ITA 40	ITA 41	ITA 42	ITA 51	ITA 52	ITA 61	ITA 62
Strap Type	Steel Strap (Regular Duty & High Tensile)						
Strap Width	13 / 16 / 19 mm	19 / 25 / 32 mm		19 / 25 / 32 mm		19 / 25 / 32 mm	
Operation	-	3 buttons	2 buttons	3 buttons	2 buttons	3 buttons	2 buttons
Tension mode	Manual	Manual	Automatic	Manual	Automatic	Manual	Automatic
Sealing	Single notch	Double notch		UPCUT seal joint Double notch		Double notch	
Dimensions	350x140x170 mm	430x260x310 mm		430x260x310 mm		430x260x310 mm	
Weight	4,0 kg	10,3 kg		11,3 kg		11,3 kg	
Pressure range	5,5 ÷ 7,0 bar	5,5 ÷ 7,0 bar		5,5 ÷ 7,0 bar		4,5 ÷ 7,0 bar	
Air Consumption	Tensioning: 12 L/s – 25cuf / min						
Joint Strength	75% of breaking strength (Variable according to the strap type)						



ITA40

Seal single notch



ITA 40 (Manual Tensioning)

STRAP		PERFORMANCE	
WIDTH	THICKNESS	TENSION FORCE MAX	TENSIONING SPEED
13 mm	0,4 ÷ 0,8 mm (Regular) 0,4 ÷ 0,63 mm (HT)	2000N (6 bar)	12 mt / min
16 mm	0,4 ÷ 0,8 mm (Regular) 0,4 ÷ 0,63 mm (HT)	5500N (6 bar)	5 mt / min
19 mm	0,4 ÷ 0,8 mm (Regular) 0,4 ÷ 0,63 mm (HT)	7500N (6 bar)	4 mt / min

ITA41 / ITA42

Seal double notch



ITA 41 (Manual Tensioning) - ITA 42 (Automatic Tensioning)

STRAP		PERFORMANCE	
WIDTH	THICKNESS	TENSION FORCE MAX	TENSIONING SPEED
19 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	9000N (6 bar)	3,8 mt / min
25 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	15000N (6 bar)	5,2 mt / min
32 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	15000N (6 bar)	5,2 mt / min

ITA51 / ITA52

Upcut double notch seal joint



ITA 51 (Manual Tensioning) - ITA 52 (Automatic Tensioning)

STRAP		PERFORMANCE	
WIDTH	THICKNESS	TENSION FORCE MAX	TENSIONING SPEED
19 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	9000N (6 bar)	3,8 mt / min
25 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	15000N (6 bar)	5,2 mt / min
32 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	15000N (6 bar)	5,2 mt / min

ITA61 / ITA62

Low air pressure - Seal double notch



ITA 61 (Manual Tensioning) - ITA 62 (Automatic Tensioning)

STRAP		PERFORMANCE	
WIDTH	THICKNESS	TENSION FORCE MAX	TENSIONING SPEED
19 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	9000N (6 bar)	3,8 mt / min
25 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	15000N (6 bar)	5,2 mt / min
32 mm	0,6 ÷ 1 mm (Regular) 0,63 ÷ 0,8 mm (HT)	15000N (6 bar)	5,2 mt / min

At low pressure (4,5bar) - Max Tension force 7000N - Tensioning speed 4mt/min

PNEUMATIC TENSIONERS AND SEALERS

For steel strap

Features

Regular duty
and high tensile steel straps
Robust and durable
Wide range of steel straps

ITA 44SP

Special design with angled
motor specifically studied
for coils application

BENEFITS

- Lightweight and easy to be used
- Strong, powerful and reliable
- Low maintenance required

ITA 44



ITA 44SP



➤ ITA 44 - ITA 44SP

POWER SUPPLY	TENSIONER
Strap Type	Steel (Standard & HT)
Strap Width	19 mm / 25 mm / 32 mm
Strap Thickness	0,6 ÷ 1,1 mm
Tension Force – Max	15000N
Tensioning speed	6 mt / min
Pressure range	5,5 ÷ 7 bar
Air consumption	12 L/s
Dimensions	340x115x90 mm (ITA 44) 230x115x250 mm (ITA 44SP)
Weight	4,3 kg
Sealing	n.a.
Joint Strength	n.a.

ITA 45



➤ ITA 45

POWER SUPPLY	SEALER
Strap Type	Steel (Standard & HT)
Strap Width	19 mm / 25 mm / 32 mm
Strap Thickness	0,6 ÷ 1,1 mm (standard) 0,63 ÷ 0,9 mm (HT)
Tension Force – Max	n.a.
Tensioning speed	n.a.
Pressure range	5,5 ÷ 7 bar
Air consumption	12 L/s
Dimensions	320x140x180 mm
Weight	2,9 kg
Sealing	Single notch
Joint Strength	75% of breaking strength (Variable according to the strap type)



BATTERY TENSIONER AND SEALER

For steel strap

Features

Battery operated tools

Regular duty & high
tensile steel strap

Strong and powerful

Reliable, robust and durable

BENEFITS

- No air connection required
- Adjustable tension (ITA 84)
- Double notch sealing (ITA 85)
- Easy to be used and low maintenance required

ITA 84



➤ ITA 84

POWER SUPPLY	TENSIONER
Strap Type	Steel (Standard & HT)
Strap Width	19 mm / 25 mm / 32 mm
Strap Thickness	0,6 ÷ 1,1 mm
Tension Force – Max	5000N ÷ 13000N
Tensioning speed	3 mt / min
Battery	Li-Ion 18V - 5Ah
Dimensions	395x120x130 mm
Weight	4,7 kg (with battery)
Sealing	n.a.
Joint Strength	n.a.

ITA 85



➤ ITA 85

POWER SUPPLY	SEALER
Strap Type	Steel (Standard & HT)
Strap Width	19 mm / 25 mm / 32 mm
Strap Thickness	0,6 ÷ 1,1 mm (standard) 0,63 ÷ 0,9 mm (HT)
Tension Force – Max	n.a.
Tensioning speed	n.a.
Battery	Li-Ion 18V - 5Ah
Dimensions	350x100x260 mm
Weight	4,5 kg (with battery)
Sealing	Seal Double Notch
Joint Strength	75% of breaking strength (Variable according to the strap type)



MANUAL TOOLS

For steel strap

Features

Lightweight
 Strong and reliable
 Robust and durable

BENEFITS

- Economical
- Easy to be used
- Low maintenance required

ITA 36



➤ ITA 36

POWER SUPPLY	MANUAL TENSIONER
Strap Type	Steel (Standard & HT)
Strap Width	19 mm / 25 mm / 32 mm
Strap Thickness	0,6 ÷ 1,1 (Regular Duty) 0,63 ÷ 0,9 (High Tensile)
Sealing	n.a.
Joint Strength	n.a.
Dimensions	500x130x360 mm
Weight	4,6 kg

ITA 30



➤ ITA 30

MANUAL SEALLES TOOL

Strap Type	Steel 13/16/19mm
Strap Thickness	0,45 ÷ 0,7 (Regular Duty) 0,45 ÷ 0,63 (High Tensile)
Tension Force – Max	6000N
Sealing	Sealless
Joint Strength	75% of breaking strength (Variable according to the strap type)
Gear ratio	1:18
Dimensions	350x140x260 mm
Weight	4,4 kg

ITA 37



➤ ITA 37

POWER SUPPLY	MANUAL SEALER
Strap Type	Steel (Standard & HT)
Strap Width	32 mm
Strap Thickness	0,6 ÷ 1,1 (Regular Duty) 0,63 ÷ 0,9 (High Tensile)
Sealing	Single notch
Joint Strength	75% of breaking strength (Variable according to the strap type)
Dimensions	610x50x165 mm
Weight	2,9 kg



TENSIONERS | For textile strap

Features

Suitable for all textile strap up to 40mm
Integrated cutting unit
Robust and strong
Aluminium cast body
Adjustable tension

BENEFITS

- Battery Operated Tool (ITA 71)
- Powerful & quick
- Easy to be used
- Low maintenance required

ITA 70



➤ ITA 70

POWER SUPPLY	PNEUMATIC
Strap Type	Textile (Woven & Composite)
Strap Width	16 mm ÷ 40 mm
Strap Thickness	0,5 mm ÷ 1,5 mm
Tension Force – Max	8000N
Tensioning speed	11 mt / min
Pressure range	5,5 ÷ 7 bar
Air consumption	12 L/s
Dimensions	330x120x160 mm
Weight	4,8 kg

ITA 71



➤ ITA 71

POWER SUPPLY	BATTERY
Strap Type	Textile (Woven & Composite)
Strap Width	16 mm ÷ 40 mm
Strap Thickness	0,5 mm ÷ 1,5 mm
Tension Force – Max	11000N
Tensioning speed	6,5 mt / min
Battery	Li-Ion 18V - 5Ah
Dimensions	400x135x190 mm
Weight	5 kg (with battery)



ACCESSORIES



**SUSPENSION
HOOK 2 POSITIONS**
Fixed

SUITABLE FOR	ITEM CODE
ITA EVO	A000225
ITA20 / ITA21 / ITA22 / ITA23	A000116
ITA24 / ITA25 / ITA27	A000155



**SUSPENSION
HOOK 3 POSITIONS**
Fixed

SUITABLE FOR	ITEM CODE
ITA24 / ITA25	A000157



**SUSPENSION
HOOK 3 POSITIONS**
With friction

SUITABLE FOR	ITEM CODE
ITA24 / ITA25 / ITA27	A000160



**VEGETAL CASE
SUSPENSION**

SUITABLE FOR	ITEM CODE
ITA20 / ITA21 / ITA22 / ITA23	A000151
ITA24 / ITA25	A000159



19 MM GUIDESTRAP KIT

SUITABLE FOR	ITEM CODE
ITA27	A000227



BUCKLE HOLDER KIT

SUITABLE FOR	ITEM CODE
ITA70 / ITA71	A000161



PROTECTION PLATE

SUITABLE FOR	ITEM CODE
ITA EVO	A000234
ITA20 / ITA21 / ITA22 / ITA23	A000137
ITA24 / ITA25	A000189
ITA27	A000158



BALANCER

BALANCER 1,5 - 3 KG. / SUITABLE FOR:	ITEM CODE
ITA18	S3000A2
BALANCER 3 - 6 KG. / SUITABLE FOR:	ITEM CODE
ITA10 / ITA11 / ITA12 / ITA14 / ITA20	S300BS1
ITA21 / ITA22 / ITA23 / ITA24	
ITA25 / ITA EVO / ITA40 / ITA44	
BALANCER 9 - 14 KG. / SUITABLE FOR:	ITEM CODE
ITA27 / ITA41 / ITA42 / ITA51	S300BS3RI
ITA52 / ITA61 / ITA62	



DRYER UNIT
Filter, pressure adjustment
and lubricator

SUITABLE FOR	ITEM CODE
ALL PNEUMATICS	S100001



AIR SPIRAL PIPE

SUITABLE FOR	ITEM CODE
TOUT PNEUMATIQUE	B100369



STRAP CUTTER

SUITABLE FOR	ITEM CODE
ALL PLASTIC AND STEEL STRAPS	S300024

BATTERY

CHARGER



BATTERY
Li-Ion 18V - 5Ah

BATTERY Li-Ion 18V - 5Ah FOR:	ITEM CODE
ITA EVO / ITA20 / ITA21 / ITA22 / ITA23 ITA24 / ITA25 / ITA84 / ITA85 / ITA71	B800580



CHARGER
Li-Ion 18V

CHARGER FOR:	ITEM CODE
ITA EVO / ITA20 / ITA21 / ITA22 / ITA23 ITA24 / ITA25 / ITA84 / ITA85 / ITA71	B800581



BATTERY-OLD
Li-Po 14,8V - 2,2Ah

BATTERY Li-Po 14,8V - 2,2Ah FOR:	ITEM CODE
ITA24-OLD	A000176



CHARGER-OLD
Li-Po 14,8V

CHARGER FOR:	ITEM CODE
ITA24-OLD / ITA25-OLD	A000186



BATTERY-OLD
Li-Po 14,8V - 3,6Ah

BATTERY Li-Po 14,8V - 3,6Ah FOR:	ITEM CODE
ITA25-OLD	A000175



RETROFIT KIT
To update ITA24 / ITA25
to the new 18V version

KIT FOR:	ITEM CODE
ITA24	A000271A
ITA25	A000272A



BATTERY
Li-Ion 36V - 2,5Ah

BATTERY Li-Ion 36V - 2,5Ah FOR:	ITEM CODE
ITA27	B800477



CHARGER
Li-Ion 36V

CHARGER FOR:	ITEM CODE
ITA27	B800560



BATTERY-OLD
Li-Po 14,8V - 2,2Ah

BATTERY Li-Po 14,8V - 2,2Ah FOR:	ITEM CODE
ITA20-OLD	A000063



CHARGER-OLD
Li-Po 14,8V

CHARGER FOR:	ITEM CODE
ITA20-OLD / ITA21-OLD / ITA23-OLD	A000091



BATTERY-OLD
Li-Po 14,8V - 3,3Ah

BATTERY Li-Po 14,8V - 3,3Ah FOR:	ITEM CODE
ITA21-OLD / ITA23-OLD	A000115



RETROFIT KIT
To update ITA20 / ITA21 / ITA23
to the new 18V version

KIT FOR:	ITEM CODE
ITA20	A000253A
ITA21	A000261A
ITA23	A000262A

