

ITA 25 – 18V

PLASTIC STRAPPING TOOL > BATTERY

Battery Strapping Tool for 16mm / 19mm - PP & PET Strap Three Operating Modes

ITA 25 is the most suitable and reliable three operating modes battery strapping tool, studied for 16/19 mm PP and PET strap.

Lightweight, well balanced, ergonomic and easy to be used also with one hand, ITA 25 can be used in fully automatic, semi-automatic and manual operating modes.

ITA 25 is equipped with Brushless motors to grant low maintenance, high speed and improved electronic control.

The high capacity Lithium-Ion battery, will grant high number of duty cycles per single charge, without any memory effect on the battery.

ITA 25 uses friction weld seal technology that guarantees high seal efficiency, without requiring any seal.

The tool finds application in many fields, from the timber to the logistic, from the steel to the building industry, or for any possible other strapping application.

ITA 25 is the battery strapping tool for plastic strap at 360°.



FEATURES

3 Operating Modes:
Automatic / Semi Automatic / Manual
Easy to be used
Digital control Panel
Brushless Motor technology

BENEFITS

Wide range & adjustable tension (500N-5500N)
Lightweight and well balanced
One hand operating tool
Easy access to wearing parts
Strong and well protected motor housing

TECHNICAL SPECIFICATION

Dimensions	340 x 150 x 160 mm 13.4" x 5.9" x 6.3"
Weight (with battery)	4.5 Kg - 10 lbs

STRAP

Type	PP and PET Strap
Strap dimension	16mm x 0,8 ÷ 1,05 mm 19mm x 0,7 ÷ 1,30 mm

POWER SUPPLY

Battery	Li-Ion 18V - 5Ah
----------------	------------------

PERFORMANCE

Min. tension force	500 N
Max. tension force	5500 N
Tensioning speed	10-12 mt/m
Sealing	Friction weld seal
Joint Strength	75% of breaking strength

* variable according to strap type

MODEL

CODE	DESCRIPTION
T2599971-18V	ITA 25 + 1 Battery + 1 Charger
T2599972-18V	ITA 25 + 2 Batteries + 1 Charger
T2599973-18V	ITA 25 + 3 Batteries + 1 Charger